



Bronze Globe Valve

ISO 9001 FM584850

2020.1

Feature


1. flange ends conform to JIS B 2011 (version 2003)
2. rising stem
3. flange ends without groove
4. Working pressure 5K (1Mpa)

Body Marking		
	2" 5K	➔

Working Pressure non Shock (unit : Kg/cm ²)	
5 Kg/cm ² under 90°C water	

Test Pressure (unit : Kg/cm ²)	
Shell (Water)	Seat (Air)
7.5	6.0

100 psi = 7Kg (7bar) = 0.7Mpa



N	Nut	Steel	1
P	Nameplate	Aluminum	1
11	Disc Gland	Brass C3604	1
10	Packing Ring	Brass C3604	1
8	Packing	Teflon	1
7	Packing Gland	Brass C3604	1
6	Handlewheel	Aluminum	1
4	Stem	Brass C36000	1
3	Disc	Bronze C84400	1
2	Bonnet	Bronze C84400	1
1	Body	Bronze C84400	1
No.	Parts	Material	Q'ty

DIMENSION

unit : mm

	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"
F	80	85	95	115	120	130	155
L	60	70	80	100	100	119	139
T	9	10	10	12	12	14	14
B	12	12	12	15	15	15	15
C	60	65	75	90	95	105	130
D	22.5	28	34.5	43.5	50	61.5	77.5
nos.	4	4	4	4	4	4	4

Note.